

Metal Letters & Logo

Rich and Crisp finishes, multiple lit options



Illuminated metal letters leave a lasting impression and get your brand noticed. Expertly crafted with premium grade stainless steel, produced in a wide range of sizes from 3" to 20" high, depth from 1" to 3", in multiple stainless finish options and lit styles.

- Premium quality and high end look
- Stainless Steel
- Stroke as thin as 1/2" (12mm)
- Size ranging from 2" to 20"
- Return depth from 1/2" to 6"
- Available in acrylic, vinyl and metal finish
- UL certified LEDs and power supplies
- 5-years warranty

Lit Type*



FRONT LIT



FRONT&SIDE
EDGE
LIT



HALO LIT

*See next page for detail.

Applications

- Building Lobby
- Retail / Storefronts Signage
- Trade Show

Get in Touch

SALES@BANDISVISION.COM



Lit Type & Material

* Color match available.

• Front & Side Edge Lit

Face : Acrylic
Return : Polished Gold or Silver
Brushed Gold or Silver
Backer : Acrylic



• Side Edge Lit / Halo Lit

Face & Return (Body) :
Polished Gold or Silver
Brushed Gold or Silver
Backer : Acrylic




• Front Lit

Face : Acrylic (with Vinyl)
Return : Steel (with Painting)




Mounting Options




Flush Mounting

(Default for Front / Side /
Front + Side Lit)




Stud Mounting


(Default for Back Lit)



Raceway Mounting




Backer Panel




LED Color Temperatures

White LED Color Temperature (Standard Color)



Tunable White



Digital LED



Wire Type


* Default Wire Length : 8' (2.4m)



Pig Tail



DC Connector



JST SM Connector

Specifications

Physical	
Max Size	20" (508mm) x 20" (508mm)
Min Size	3" (76mm) x 3" (76mm)
Thickness	1" (25mm) or 1 3/16" (30mm) or 1 3/8" (35mm)
Operating Temperature	-30°C (-22°F) ~ +40°C (+104°F)
Environment	Dry location only (Indoor)
Warranty	5 Years

Electrical	
Input Voltage	12V / 24V DC Class 2
Power Consumption	2.2w/ft (Standard) / 3w/ft (High-Lumn)
Brightness	2,000 Lux to 10,000 Lux
Color Temperature	White LED / Tunable White / R or G or B / RGB / RGBW / Digital LED
Wire Size	20 AWG 2 Wire (Standard)
UL Listed	Yes
CRI	90+